

FLEXITALLIC L.P.

Material Safety Data Sheet

No. FDP-026

REVISED: 13 July 2009

Contact Number 281-604-2400

GENERAL INFORMATION

Manufacturer:
Flexitallic Limited
6915 La Porte Road
Deer Park, TX 77536

Common Name, Trade Name, or Specification:

PTFE Tape

DOT Hazard Code - N/A

1. HAZARDOUS INGREDIENTS AND EXPOSURE LIMITS

Although several of the ingredients used to formulate this product may be hazardous in the raw state, the manufacturing process results in a solid, infusible form, binding or otherwise rendering the mixture inert. We have identified below those hazardous constituents present in quantities greater than 1% (0.1% for carcinogens) that may be released from the product by overheating, burning, machining, abrading, or riveting.

Component	CAS Number	%	OSHA PEL	ACGIH TLV
Rubber	None	<25	N/A	N/A
PTFE Binder	None	<50	N/A	3 ppm(HFl)/2ppm(CFl)

2. PHYSICAL AND CHEMICAL CHARACTERISTICS

Melting Point - None

Solubility in water - Insoluble

Odor -None

Color - White

Specific Gravity - 0.4 - 0.5

Form - Solid

3. FIRE AND EXPLOSION DATA

Auto-ignition Temperature: This product is inherently flame resistant.

Flammable Limits in Air: % in Air by Volume: LEL: N/A UEL: N/A

Extinguisher Media: Carbon dioxide, chemical, or foam

Special Firefighting Procedure: Material in or near fires should be cooled with a water spray or fog. A self-contained breathing apparatus, operating in the positive pressure mode, and full fire fighting protective clothing should be worn for combative fires.

Unusual Fire and Explosion Hazards: Thermal decomposition or combustion may produce dense smoke, oxides of carbon, and low molecular weight organic compounds whose composition has not been characterized.

4. PHYSICAL HAZARDS AND REACTIVITY DATA

Stability: Stable at normal temperatures and storage conditions

Incompatibility: None

Hazardous Decomposition Products: None

Hazardous Polymerization: Will not polymerize. This product is fully cured in the manufacturing process.

5. HEALTH HAZARDS

Carcinogenicity:	NTP Listed	IARC Listed	NIOSH Listed	OSHA Listed
Rubber	No	No	No	No
PTFE Binder	No	No	No	No

Symptoms and Effects of Exposure to the Individual Components:

PTFE (Teflon®)

Inhalation of fumes from overheating PTFE may cause polymer fume fever, a temporary flu-like illness with fever, chills, and sometimes cough, of approximately 24 hours duration. Smokers should avoid contamination of tobacco products, and should wash their hands before smoking. Small amounts of carbonyl fluoride and hydrogen fluoride may also be evolved when PTFE is overheated or burned.

Inhalation of low concentrations of Hydrogen Fluoride can initially include symptoms of choking, coughing, and severe eye, nose and throat irritation. Possibly followed after a symptomless period of 1 to 2 days by fever, chills, difficulty in breathing, cyanosis, and pulmonary edema. Acute or chronic overexposure to HF can injure the liver and kidneys.

Inhalation, ingestion, or skin or eye contact with Carbonyl fluoride may initially include: skin irritation with discomfort or rash; eye corrosion with corneal or conjunctival ulceration; irritation of the upper respiratory passages; or temporary lung irritation effects with cough, discomfort, difficulty breathing, or shortness of breath.

Individuals with preexisting diseases of the lungs may have increased susceptibility to the toxicity of excessive exposures from thermal decomposition products.

RUBBER (POWDERED)

Inhalation hazards - May cause mild irritation of respiratory tract. Repeated and prolonged inhalation of dust may lead to a benign pneumoconiosis. This condition may cause some lung function impairment but is reversible with reduced exposure. **Other hazards** - Eyes - may cause mild transient eye irritation.

6. FIRST AID

Inhalation: Move to fresh air. Obtain medical attention.

Eyes: Flush with water to remove particulate. Obtain medical attention.

Skin: Wash thoroughly with soap and water. If persistent irritation develops, obtain medical attention.

Ingestion: Obtain medical attention.

7. SPECIAL PRECAUTIONS AND SPILL / LEAK PROCEDURES

Handling and Storage : Shipping and storage may result in accumulation of dust in shipping containers. If this occurs, dispose of the container in an airtight polyethylene bag (see disposal instructions below) or remove dust by vacuuming or wet mopping. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust from storage containers.

Release or Spill : If a release of dust occurs during machining, abrading, or riveting, remove dust by vacuuming or wet mopping. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust from the workplace.

Waste Disposal : Disposal of solid waste is regulated by federal and state law. Waste should be placed in airtight containers, and disposed of properly. Contact local regulatory agency for guidance.

8. PERSONAL PROTECTION AND CONTROL

Respiratory Protection : Use NIOSH-approved respirator if exposure to dust, vapors, or fumes in concentrations exceeding PEL's or TLV's is possible. (See 29 CFR 1910.134 for respiratory protection standards)

Ventilation : Any operations which may produce dust, including machining, grinding, riveting, or abrading of this product, should be adequately exhausted to prevent inhalation of dust.

Personal Protective Equipment : Suitable respiratory protection should be worn if dust exposure is possible. All regulations and safe practices related to the use of respiratory protection must be observed. Refer to OSHA standards and NIOSH guidelines. If skin irritation occurs, gloves and other protective garments may be worn.

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date of revision. Flexitallic, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability, including direct, incidental or consequential damages for any reliance thereon.

This MSDS should not be used as a complete or accurate summary of the content of the product. For specific information on brand names, manufacturers, or quantities, please refer to specific product specification documents where available.